Development of an Arduino-based Solar Power Tracking System

Ophelia M. Boligor, Ramer Allen F. Montilla, Christian Laurince D. Cocon, Ydron Paul C. Amarga, Jeffrey T. Dellosa Department of Electronics Engineering (DECE), College of Engineering and Geosciences (CEGS) Center for Renewable Energy, Automation and Fabrication Technologies (CRAFT) Caraga State University, Butuan City, Philippines

Abstract:- The use of fossil fuels and non-renewable resources to fuel our industry has an adverse effect on the environment. The use of solar power can be constructive in minimizing carbon emissions to the atmosphere. However, photovoltaic potential from the sun is not fully utilized due to some restrictions, and a solar tracking system is used to increase the efficiency of the energy harvested from the sun. Creating an affordable yet easily operated solar tracking machine will benefit the environment. A linear actuator and an RTC are used to manage the system with a time-based mechanism.

Keywords:- renewable energy, solar-tracker, solar power.

I. INTRODUCTION

Renewable power sources have become the alternatives for fossil fuels, and the usage of fossil fuels has shown adverse effects on the environment; using renewable power sources such as solar, wind, hydroelectric and geothermal is considered environmentally friendly and sustainable [1-3]. Replacing fossil fuels with sustainable energy has become a trend in innovation and technology because it has shown over the years that using fossil fuels as the primary source of power in many countries has led to an alarming rise in carbon emissions, which are the majority source of greenhouse gases (GHGs) in the atmosphere [3-5]. The United Nations (UN) utmost importance of sustainable emphasized the development worldwide in 2015 with one of its goals of achieving affordable and clean energy and ensuring energy efficiency [6]. The promotion of renewable energy has become the standard agenda for many policymakers and to raise awareness of the harmful effects of the consumption of fossil fuels in countries with high dependency on coal, oil, and gas; solar energy has become known worldwide for it is one of the cleanest energy sources [1-8].

Solar is the most attractive renewable energy source and several studies have been conducted with the use of solar energy [9-13]. Solar power is used to provide electrification in the rural areas [9]. Even today, solar power is being implemented in water bodies such as lake through floating technologies [10]. Solar is being developed as well to advance its state with the implementation of artificial intelligence [11-13].

Solar energy has been commercially used since 1954, and the use of solar photovoltaic was made possible by the discovery of Edmund Becquerel in 1839 through his observation of the direct light that strikes one of the electrodes of an electrolyte process, the voltage generated is called the effect photovoltaic[14]. This new renewable power source has become the new way of generating electricity, making it the third most significant energy source after hydro and wind [15].



Fig. 1: Correlation heatmap of the Renewable Energy Index with selected socioeconomic indicators. The numeric values are Pearson Correlation Coefficients (r). Values greater than 0.2 indicate numeric association [13]

However, the efficiency of PV-based power in many cities in the world is still not considered economically reasonable compared to the current sources of energy [15]. Therefore, many academic and industrial research groups are still trying to improve the efficiency and the invention of PV conversion equipment; one way to enhance the performance and the efficiency of PV solar systems is to use a solar tracking system [16]. Compared to static solar panels, which are positioned at a constant angle, limiting the energy harvesting to only a few hours a day [17]– the solar panel's solar–tracking system has shown 30-60% of the PV yield [18].

II. OBJECTIVES

The implementation of the solar tracker system is proven to improve the efficiency of energy harvesting of solar panels. An estimated 384.6 yotta watts of energy in the time during daytime and completely shut off during night time.

The overall objective of this project is to design and develop a single-axis solar panel with a solar tracking system. The system will be able to track the motion of the. The specific objectives of the projects are:

- To control the position of a solar panel in accordance with the motion of the sun.
- To increase the amount of solar energy received by the solar panel using a tracking system.



Fig. 2: Photovoltaic Potential of the World [10]

forms of light and other forms of radiation are produced by the sun, the Earth approximately receives1,000W/m2on a clear day [17]; however, most of this energy is lost due to the positioning of the panel. According to the report from the Global Solar Atlas, the Philippines has a great photovoltaic potential all over the country. The image shows that most potential for photovoltaic power is located mostly in the Luzon region of the country [18].



Fig. 3: Photovoltaic Potential of the Philippines [19]

III. MATERIALS AND METHODS

A. Hardware Materials and Equipment

The following materials and equipment are used in designing the prototype of the single-axis solar tracker for the solar panel:

- Arduino Uno R3
- Linear Actuator
- 100 W Solar panel
- 12V Battery
- Solar Charge Controller
- L298N Motor Driver Module
- Real-Time Clock
- Bearings
- Wires
- Bolts and Screw
- Wood for the base and stand

The Arduino Uno microcontroller hardware is a very popular choice in programmable devices. This has been proven to work in various development projects [20-26]. The intellectual property for the developed device using the Arduino microcontrollers may be subject to the intellectual property policy of the university [27].

B. Software used in the project

Arduino Software IDE includes a code editor, a message area, a text console, a toolbar with buttons for common functions, and a series of menus. It communicates with the Arduino hardware and uploads applications to it.

In designing and developing this project, three main components were implemented; (i) construction of the frame and circuitry, (ii) installation of hardware components, and (iii) development of the program to control the linear actuator. The flowchart of the overall system is shown in the figure below.

C. Connecting the Hardware Components

The Arduino board serves as the circuit's brain. A Linear actuator is used to position the solar panel where maximum solar energy is achieved. A Real-time Clock (RTC) will determine the position of the solar panel. The linear actuator is connected to the load output of the solar charge controller; the battery is also connected to the solar charge controller that will power the L298N Motor Driver Module. The Motor Driver is connected to the actuator and Arduino Uno board.



Fig. 4: Flowchart of the Overall System

D. Arduino Program for Solar Tracking Device

Once the hardware is ready, connect the Arduino Uno board to the computer and start programming. Start up the code by including libraries and defining all the pins used. Download the RTClib from the Library Tools of the Arduino IDE, as well as the Linear Actuator Library.

<pre>Not in the interval inter</pre>	Coll 102, med Property Select Indexes (Actives 1.4.19	- 0 ×
<pre>Interference.org I</pre>		8
<pre>billing responses to the start of the second of the s</pre>	LCDD_InProc_Sources	
<pre>til terstelligt til Statting til Stat</pre>	estelado "watolar" Finelado "WETOLA"	
<pre>Hit Status Hay</pre>	int autor2-11	
<pre>int Status Status int Status Status Status Status int Status Status Status int Status Status Status Status int Status Status Status Status int Status Status Status Status Status int Status S</pre>	RTC DS221 rts;	
<pre>int =</pre>	bool Mighteime = inlos	
<pre>static_set(s) static_set(</pre>	char dayaufthemeek[7][24] = ["monday", "monday", "monday", "medneeday", "vioureday", "milday", "maturday");	
<pre>min_property // set // se</pre>	vaid setup () [Sector Device (SEGM)]	
<pre>press(); ======;; if (100, ======; (100, ==:; (100, ==:; (100, ==:; (100, ==:; (100, ==:; (100, ==:; (100, =:=:; (100, =:=:; (100, =::; (100, ::; (100, ::; (100, ::; (100, ::; (100, ::; (100, :</pre>	delay(\$000)) // wait for compole opening	
<pre>i de de la de</pre>	pinNode(11, GUTPIT))	
<pre>plant(); } * * * * * * * * * * * * * * * * * *</pre>	is (Interlegin()) Serial crimels("Coulds's first \$20");	
<pre>/* (* (********************************</pre>	shile (D)	
<pre>"bit bit bit bit """"""""""""""""""""""""""""""""""""</pre>	(f. (vro. Jastienev (f.).)	
• Control of the second of the seco	Social.println("MIP lost power, lets set the time!");	
<pre>></pre>		
<pre>></pre>		
• • • • • • • • • • • • • • • • • • •		
<pre>Publics/Packaterial / Ameri 1/y To To the task has task Publics/Packaterial / Ameri 1/y To To the task has task Publics/Packaterial / Public / Public</pre>	<i>b</i>	Access the or COM
• • • • • • • • • • • • • • • • • • •		
<pre>PutUp rest () PutUp rest () P</pre>		
••••••••••••••••••••••••••••••••••••	C LLLLIG_Instituted and Active 1.419 File for Such Task Labo	- a ×
<pre>LimitLorence_doursel Limi</pre>		ø
<pre>1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1</pre>	LECHI_INTPort_Stational Literal_usi(DateTime(F)_DKTE_), F1_2DEE_1));	
<pre>rel res 0 i i i i i i i i i i i i i</pre>	1	
<pre>1</pre>	veid loop ()	
<pre>ii (constant) ************************************</pre>	Baterise nos = sternos();	
<pre>//</pre>	<pre>11 ((now.hour() >> 8 if now.hour() <> 17) if now.minute() => 0 if [MotorRunning if now.second()>>> 0 if now.second() <> 10)] MotorRunning = true; </pre>	
<pre>style="text-s</pre>	// upward Serial.println("Moving upward");	
<pre>static contained a contai</pre>	algatelentite (voter2, 200); digitalarite (voter2, 2100); dal u(200);	
 	else (f(nux.espond()>=50) (
<pre>International (Second Second Sec</pre>	delay(2000); Meterfunning = 101992	
// sec sectors (sector) // sectors (sector) // s	1 17 (nov.hour() == 18)]	
<pre>style="text-s</pre>	// down Semial.println("Noving downward");	
###/(5000) ■ • ###/(5000) ■ • ###/(5000) ■ • ###/(5000) ■ • ###/(5000) ■ • ###/(5000) ■ • ###/(5000) ■ • ###/(5000) ■ • ###/(5000) ■ • ###/(5000) ■ • ###/(5000) ■ • ###/(5000) ■ • ###/(5000) ■ • ###/(5000) ■ • ###/(5000) ■ • ###/(5000) ■ • ###/(5000) ■ • ####/(5000) ■ • ####/(5000) ■ • ####/(5000) ■ • ####/(5000) ■ • ####/(5000) ■ • #####/(5000) ■ • #####/(5000) ■ • ####################################	<pre>digitalsrise(wonart, with); digital#site(astus2, 1000);</pre>	
<pre>Subject statistics from '19' to a statistic statistic statistics and statistic statistics and statistics a</pre>	delay(%6000);	
<pre></pre>		
• • • • • • • • • • • • • • • • • • •		
<pre>c display the second of t</pre>	ð	Assess and or COVP
<pre>c d x tb (g is pin to b) tb</pre>		
<pre> Comparison Comparison</pre>	S UCINE(mel/hold) John III/V Ele Est Swith Took Lielp	- a ×
<pre>Listing the function of t</pre>		2
<pre>work1.print(work1.msv); dip(dip(int).msv); dip</pre>	ECERTICAN Provident Control And	
<pre>statistic Unite Spatter; 5:00; in the United Spatter; 5:00; in the Un</pre>	<pre>serial.printls("noving dommard"); digitalWrite(motori, WICH);</pre>	
Marking Specific ("Supreme Specific Specifi	digitalWrite (matorz, 1000); delwy (Sfond);	
Testad::picker(')') Testad::picker(')') Featad::picker(')) Testad::picker(')')	 Serial.println("Current Date 4 Zime: "); Serial.print(nt(new.waar(), 000))	
implementary implementary<	Secial print(//)) Secial print(//)) Secial print(//))	
Testaki, yisht(""); Content ("); Testaki, yisht("); Content (");	Section (v(*)) Section (v(*)) Section (v(*))	
<pre>swcist_print(") ">) Fund_print(") ">) Fund_print(") ">) Fund_print(") ">>> Fund_print(") ">>>> Fund_print(") ">>>>>>>>>>>>>>>>>>>>>>>>>>>>>>>>>>></pre>	Social.print(" ("); Secial.print(days0f2bsWeek[now.day0f2bsWeek[)]);	
aments restor (* 17) March (* 10) March (* 10) Seetal, szánt (sz	serial.print(") ")) Serial.print(nos.hour(), DEC))	
Reals_statutor_execution, 1857; setters_statutor_statut	Section (France (1977) Section (Association (1978)) Section (1979)	
state(1000);	Serial.print(now.second(), DEC); Serial.print(n();	
	dolay(1000);	

Fig. 5: Programming codes shown for the automation of the device developed

IV. RESULTS AND DISCUSSIONS

The implementation of a solar tracking system for solar panels is applied to get maximum power output from the sun. The prototype of the solar-tracker project is equipped with RTC that will determine the position of the solar panel in accordance with the time during the daytime. This design is an effective method of implementing a single-axis solar tracking system, and a single-axis solar tracker is more likely to be used in the utility sector because it costs less than the dual-axis solar tracker.



Fig. 6: Linear actuator of the system



Fig. 7: The system as designed and implemented.



Fig. 8: Arduino microcontroller and system developed.

The mechanism used in the solar tracking system for the prototype is a linear actuator. As shown in figure 5, the linear actuator will push one side of the solar tracking system to tilt it upward and will contract back to tilt it back to the other side.

ISSN No:-2456-2165

The use of the linear actuator and RTC is an effective method of designing a single-axis solar panel with the help of Arduino Uno R3. This design of solar tracker is less expensive and much easier to operate.An RTC is used to control the movement of the linear.

The actuator is programmed to control the movement of the linear actuator to move hourly during the day; the operation will start at 8:00 AM and will end at 5:00 PM. At the end of the program, the operation will return back to the



original state and will start the next day again. Fig. 9: Design of the system as implemented

V. CONCLUSION

The system's protection is also essential for the Solar tracker. The solar tracker must be installed in an area with no obstruction that prevents the solar tracker from harvesting maximum energy from the sun. However, it can also be prone to damage caused by rain, wind, etc. Thus, the researchers must create a casing that will protect the circuit from these environmental damages.

The current project is a single-axis solar tracker which tracks the sun's movement from east to west. The sun changes its position on the Earth's atmosphere due to Earth's revolution around the sun, so the light we get from the sun will not always be in the exact longitude and latitude coordinates. A dual-axis solar tracking system is recommended to collect the maximum energy harvested from the sun.

VI. RECOMMENDATION

The system's protection is also essential for the solar tracker. The solar tracker must be installed in an area with no obstruction that prevents the solar tracker from harvesting maximum energy from the sun. However, it can also be prone to damage caused by rain, wind, etc. Thus, the researchers must create a casing that will protect the circuit from these environmental damages. The current project is a single-axis solar tracker which tracks the sun's movement from east to west. The sun changes its position on the Earth's atmosphere due to Earth's revolution around the sun, so the light we get from the sun will not always be in the exact longitude and latitude coordinates. A dual-axis solar tracking system is recommended to collect the maximum energy harvested from the sun.

REFERENCES

- [1.] I. Jawad Hashim," A New Renewable Energy Index," 2021 6th International Conference on Renewable Energy: Generation and Applications (ICREGA), 2021, pp. 229-232, DOI: 10.1109/ICREGA50506.2021.9388297.
- [2.] F. Halicioglu and N. Ketenci, "Output, renewable and non-renewable energy production, and international trade: Evidence from EU-15 countries," Energy, vol.159, pp. 995–1002, Sep. 2018, DOI: 10.1016/j.energy.2018.06.197
- [3.] Calimpusan, R. A. C. O., Trajano, R., Yungao, A., & Dellosa, J. T. (2021, December). Water Purification System Powered by a Mini Hydroelectric Power System. In 2021 6th International Conference on Development in Renewable Energy Technology (ICDRET) (pp. 1-6). IEEE.
- [4.] Dellosa, J. T. (2016). Potential Effect and Analysis of High Residential Solar Photovoltaic (PV) Systems Penetration to an Electric Distribution Utility (DU). International Journal of Renewable Energy Development, 5(3).
- [5.] H. Allamehzadeh," An Update on Solar Energy and Sun Tracker Technology with a Dual Axis Sun Tracker Application," 2019 IEEE 46th Photovoltaic Specialists Conference (PVSC), 2019, pp. 2037-2044, DOI: 10.1109/PVSC40753.2019.8981360.
- [6.] Dellosa, J. T. (2015, June). Financial payback of solar PV systems and analysis of the potential impact of netmetering in Butuan City, Philippines. In 2015 IEEE 15th International Conference on Environment and Electrical Engineering (EEEIC) (pp. 1453-1458). IEEE.
- [7.] P. Ramirez-Del-Barrio et al.," Sustainable development through the use of solar energy for productive processes: The Ayllu Solar Project," 2017 IEEE Global Humanitarian Technology Conference (GHTC), 2017, pp. 1-8, DOI: 10.1109/GHTC.2017.8239310.
- [8.] Dellosa, J. T., Panes, M. J. C., & Espina, R. U. (2021, September). Techno-Economic Analysis of a 5 MWp Solar Photovoltaic System in the Philippines. In 2021 IEEE International Conference on Environment and Electrical Engineering and 2021 IEEE Industrial and Commercial Power Systems Europe (EEEIC/I&CPS Europe) (pp. 1-6). IEEE.
- [9.] Masih and I. Odinaev," Performance Comparison of Dual Axis Solar Tracker with Static Solar System in Ural Region of Russia," 2019 Ural Symposium on Biomedical Engineering, Radioelectronics and Information Technology (USBEREIT), 2019, pp. 375-378, DOI: 10.1109/USBEREIT.2019.8736642.
- [10.] Dellosa, J., & Palconit, E. V. (2022). Resource Assessment of a Floating Solar Photovoltaic (FSPV) System with Artificial Intelligence Applications in Lake Mainit, Philippines. Engineering, Technology & Applied Science Research, 12(2), 8410-8415.
- [11.] Kurukuru, V. S. B., Haque, A., Khan, M. A., Sahoo, S., Malik, A., & Blaabjerg, F. (2021). A review on artificial intelligence applications for grid-connected solar photovoltaic systems. Energies, 14(15), 4690.

ISSN No:-2456-2165

- [12.] Dellosa, J. T., & Palconit, E. C. (2021, September). Artificial Intelligence (AI) in Renewable Energy Systems: A Condensed Review of its Applications and Techniques. In 2021 IEEE International Conference on Environment and Electrical Engineering and 2021 IEEE Industrial and Commercial Power Systems Europe (EEEIC/I&CPS Europe) (pp. 1-6). IEEE.
- [13.] Mellit, A., & Kalogirou, S. (2021). Artificial intelligence and internet of things to improve efficacy of diagnosis and remote sensing of solar photovoltaic systems: Challenges, recommendations and future directions. Renewable and Sustainable Energy Reviews, 143, 110889.
- [14.] Dellosa, J. T., & Barocca, R. B. (2021, September). Techno-economics and programs of rural electrification using solar energy in South and Southeast Asia. In 2021 IEEE International Conference on Environment and Electrical Engineering and 2021 IEEE Industrial and Commercial Power Systems Europe (EEEIC/I&CPS Europe) (pp. 1-6). IEEE.
- [15.] H. Allamehzadeh," Solar energy overview and maximizing power output of a solar array using sun trackers," 2016 IEEE Conference on Technologies for Sustainability (SusTech), 2016, pp. 14-19, DOI: 10.1109/SusTech.2016.7897136.
- [16.] N. Mamun et al.," Multi-directional solar tracker using low cost photo sensor matrix," 2014 International Conference on Informatics, Electronics & Vision (ICIEV), 2014, pp. 1-5, DOI: 10.1109/ICIEV.2014.7136008.
- [17.] Sawant, D. Bondre, A. Joshi, P. Tambavekar and A. Deshmukh, "Design and Analysis of Automated Dual Axis Solar Tracker Based on Light Sensors," 2018 2nd International Conference on I-SMAC (IoT in Social, Mobile, Analytics, and Cloud) (I-SMAC)I-SMAC (IoT in Social, Mobile, Analytics, and Cloud) (I-SMAC), 2018 2nd International Conference on, 2018, pp. 454-459, DOI: 10.1109/I-SMAC.2018.8653779.
- [18.] K. Suria and R. M. Idris, "Dual-axis solar tracker based on predictive control algorithms," 2015 IEEE Conference on Energy Conversion (CANCON), 2015, pp. 238-243, DOI: 10.1109/CENCON.2015.7409546.
- [19.] https://globalsolaratlas.info/map?c=11.609193,8.4375,3.
- [20.] I. Jawad Hashim," A New Renewable Energy Index," 2021, 6th International Conference on Renewable Energy: Generation and Applications (ICREGA), 2021, pp. 229-232, DOI: 10.1109/ICREGA50506.2021.9388297.
- [21.] Armando R.Guzman Jr; Ronnel O. Cacho; Ennea Theresa O. Durango; Isagani M. Roma; Jr., Lovely Mae Dagsa; Jeffrey T. Dellosa. "Self-Powered Griller using Thermoelectric Generator Peltier Module with Backup Power Source." Volume. Volume. 7 Issue. 4, April -2022, International Journal of Innovative Science and Research Technology (IJISRT), www.ijisrt.com. ISSN -2456-2165, PP :- 944-949. https://doi.org/10.5281/zenodo.6551708
- [22.] Sonza, M. K. S., Quitasol, J. L., Recimo, J. R. M., Lloren, L. B., & Dellosa, J. T. Design and Prototype Development of a Self-Cleaning Portable Air Conditioning Device and System. change, 3, 13.

- [23.] Mark Kelvin S. Sonza; Jhorkid L. Quitasol; Jay Rico M. Recimo; Lloyd B. Lloren; Jeffrey T. Dellosa. "Design and Prototype Development of a Self-Cleaning Portable Air Conditioning Device and System." Volume. Volume. 7 Issue. 4, April - 2022, International Journal of Innovative Science and Research Technology (IJISRT), www.ijisrt.com. ISSN - 2456-2165, PP :-356-362. https://doi.org/10.5281/zenodo.6505324
- [24.] Baba, M. C., Grado, J. J. B., Solis, D. J. L., Roma, I. M., & Dellosa, J. T. A Multisensory Arduino-Based Fire Detection and Alarm System using GSM Communications and RF Module with an Android Application for Fire Monitoring. International Journal of Innovative Science and Research Technology (IJISRT), www. ijisrt. com. ISSN-2456-2165, PP:-964-968. https://doi.org/10.5281/zenodo, 6433836.
- [25.] Guzman Jr, A. R., Cacho, R. O., Durango, E. T. O., Roma Jr, I. M., Dagsa, L. M., & Dellosa, J. T. Self-Powered Griller Using Thermoelectric Generator Peltier Module with Backup Power Source.
- [26.] Mike C. Baba; JL-Joshua B. Grado; Dean Joshua L. Solis; Isagani M. Roma; Jeffrey T. Dellosa. "A Multisensory Arduino-Based Fire Detection and Alarm System using GSM Communications and RF Module with an Android Application for Fire Monitoring." Volume. Volume. 7 Issue. 3, March 2022, International Journal of Innovative Science and Research Technology (IJISRT), www.ijisrt.com. ISSN 2456-2165, PP :- 964-968. https://doi.org/10.5281/zenodo.6433836
- [27.] Dellosa, J. T. (2017, April). The impact of the innovation and Technology Support Offices (ITSOs) on innovation, intellectual property (IP) protection and entrepreneurship in philippine engineering education. In 2017 IEEE Global Engineering Education Conference (EDUCON) (pp. 762-770). IEEE.